



CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

## Introducing the Grizzly Model G9984 3HP Industrial Oscillating Edge Sander



### **MACHINE HIGHLIGHTS (see *Machine Data Sheet* for full specifications)**

- 3 HP, 220V, single-phase motor.
- Belt speed is 4120 FPM with  $\frac{1}{4}$ " oscillation stroke.
- Uses a  $138\frac{1}{2}$ " x 9" sanding belt and a  $47\frac{1}{2}$ " x  $9\frac{1}{2}$ " platen.
- Features an edge sanding table and contour sanding table that both adjust within an 8" range.
- Edge sanding table tilts from 0–45°.

The Model G9984 3HP Industrial Oscillating Edge Sander is available for \$2,995.00. As with all Grizzly products, the Model G9984 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit [www.grizzly.com](http://www.grizzly.com).



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G9984 INDUSTRIAL OSCILLATING EDGE SANDER, 3 HP SINGLE-PHASE

### Product Dimensions:

Weight..... 682 lbs.  
Length/Width/Height..... 82 x 24 x 45-1/2 in.  
Foot Print (Length/Width)..... 42 x 24-1/2 in.

### Shipping Dimensions:

Type..... Wood Crate  
Content..... Machine  
Weight..... 873 lbs.  
Length/Width/Height..... 28 x 86 x 45 in.

### Electrical:

Minimum Circuit Size..... 20 amp  
Switch..... Magnetic with Thermal Protection  
Switch Voltage..... 220V  
Cord Length..... 7 ft.  
Cord Gauge..... 12 gauge  
Plug Included..... No

### Motors:

#### Main

Type..... TEFC Capacitor Start Induction  
Horsepower..... 3 HP  
Voltage..... 220V  
Prewired..... 220V  
Phase..... Single  
Amps..... 18A  
Speed..... 1725 RPM  
Cycle..... 60 Hz  
Number Of Speeds..... 1  
Power Transfer ..... Direct Drive  
Bearings..... Shielded and Lubricated

### Main Specifications:

#### Operation Information

Sanding Belt Speed..... 4120 FPM  
Sanding Belt Oscillations..... 1/4 in.  
Sanding Belt Length..... 138-1/2 in.  
Sanding Belt Width..... 9 in.

**Table Information**

Table Length.....	47-3/4 in.
Table Width.....	11-3/4 in.
Table Thickness.....	1-1/4 in.
Table Tilt.....	0 to 45 deg.
Table Travel.....	8 in.
Floor To Table Height.....	33 - 41 in.
End Table Length.....	18 in.
End Table Width.....	13 in.
End Table Thickness.....	1-1/4 in.
End Table Travel.....	8 in.

**Platen Information**

Platen Type.....	Graphite Coated
Platen Length.....	47-1/2 in.
Platen Width.....	9-1/2 in.

**Construction**

Table Construction.....	Aluminum
Frame Construction.....	Cast Iron
Base Construction.....	Sheet Steel
Drive Roller Construction.....	Rubber
Idler Roller Construction.....	Rubber
Paint.....	Epoxy

**Other Related Information**

No Of Dust Ports.....	1
Dust Port Size.....	4 in.
Belt Release.....	Quick Release Lever
Drive Roller Size.....	9 in.
Idler Roller Size.....	4 in.

**Other Specifications:**

Country Of Origin .....	Taiwan
Warranty .....	1 Year
Serial Number Location .....	ID Label Below Grizzly Nameplate

**Features:**

- Miter Work Stop
- Quick Belt Release Lever
- Conveniently Located Belt Tracking and Tension Adjustment
- 1/4" Belt Oscillation
- Spring Adjusted Table for Easy Movement
- Two Large Sanding Tables