



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0538 1/3 HP OSCILLATING SPINDLE SANDER

Product Dimensions:

Weight..... 34 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 20 x 14 x 11-1/2 in.
Footprint (Length x Width)..... 20 x 14 in.

Shipping Dimensions:

Type..... Cardboard
Content..... Machine
Weight..... 37 lbs.
Length x Width x Height..... 22 x 16 x 18 in.

Electrical:

Power Requirement..... 110V, Single-Phase, 60 Hz
Minimum Circuit Size..... 15A
Switch..... Toggle Safety Switch with Locking Tab
Switch Voltage..... 110V
Cord Length..... 9 ft.
Cord Gauge..... 18 Gauge
Plug Included..... Yes
Included Plug Type..... NEMA 5-15

Motors:

Main

Type..... Universal
Horsepower..... 1/3 HP
Voltage..... 110V
Phase..... Single
Amps..... 4A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer Direct
Bearings..... Sealed and Permanently Lubricated

Main Specifications:

Table Info

Table Width..... 14 in.
Table Length..... 20 in.
Table Thickness..... 1 in.
Table Opening..... 3-1/2 in.
Table Inserts..... 13/16, 1-1/16, 1-5/16, 1-13/16, 2-5/16, 3-5/16 in.

Spindle Info

Spindle Diameter..... 1/2, 3/4, 1, 1-1/2, 2, 3 in.
Spindle Lengths..... 4-1/2 in.
Spindle Speed..... 1725 RPM
Spindle Oscillation..... 72 SPM
Stroke Length..... 5/8 in.
Arbor Size..... 1/2 in.
Total Arbor Length..... 4-1/2 in.

Construction

Base..... Plastic
Table..... Particle Board with Plastic Laminate
Frame..... Plastic

Other

No. Of Dust Ports..... 1
Dust Port Size..... 2-1/2 in.

Other Specifications:

Country Of Origin China
Warranty 1 Year
Serial Number Location On Front
Assembly Time 20 Minutes

Features:

- Paddle On/Off Switch with Lock
- Six 4-1/2 in. Tall Sanding Drums
- Compact Size for Easy Storage
- Three 80 gr. Sleeves (1/2", 1" and 2")
- Three 150 gr. Sleeves (3/4", 1-1/2" and 3")
- Six Table Inserts