



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1168 1 HP 4-SPEED TRACK POWER FEEDER, 3-PHASE

Product Dimensions:

Weight..... 139 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 43-1/4 x 23-1/2 x 29-1/2 in.
Footprint (Length x Width)..... N/A x N/A

Shipping Dimensions:

Carton #1

Type..... Cardboard Box
Content..... Machine
Weight..... 72 lbs.
Length x Width x Height..... 30 x 12 x 23 in.
Must Ship Upright..... No

Carton #2

Type..... Cardboard Box
Content..... Stand
Weight..... 82 lbs.
Length x Width x Height..... 13 x 11 x 30 in.
Must Ship Upright..... No

Electrical:

Power Requirement..... 220V, 3-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 3.4A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 9 ft.
Power Cord Gauge..... 16 AWG
Plug Included..... No
Recommended Plug Type..... 15-15
Switch Type..... Forward/Reverse Switch with 2 Speeds
Recommended Phase Converter..... G5841

Motors:

Main

Horsepower..... 1 HP
Phase..... 3-Phase
Amps..... 3.4A/2.5A
Speed..... 3400 / 1720 RPM
Type..... TEFC Induction
Power Transfer Gear Drive
Bearings..... Sealed & Permanently Lubricated
Centrifugal Switch/Contacts Type..... N/A

Main Specifications:

Workpiece Capacities

Minimum Workpiece Length..... 8 in.

Operation Info

Number of Feed Speeds..... 4
Feed Speeds..... 14.5, 29, 39, 78 FPM
Swing..... 360 deg.
Vertical Movement..... 9-1/2 in.
Horizontal Movement..... 24-1/4 in.
Rotation..... Forward, Reverse

Roller Info

Number of Rollers..... 5
Roller Suspension..... 3/4 in.
Maximum Height Rollers Parallel Table Surface..... 8-1/2 in.

Track Info

Number of Track Pieces..... 3
Track Width..... 1/2 in.
Track Length..... 44 in.

Construction Info

Roller..... Synthetic Rubber
Housing..... Cast Aluminum
Supports..... Cast Iron
Column..... Steel
Paint Type/Finish..... Enamel

Other

Column Diameter..... 2-1/4 in.

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 45 Minutes
Serial Number Location Checked Sticker, On Out-feed Portion Of Housing's Roller / Belt Cover Side
ISO 9001 Factory Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) No

Features:

Rollers are Spring Tensioned with 3/4" Travel
Heavy-Duty Gear Reduction with Hardened Gears
Universal Positioning with Handle Locks