



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G9922 OSCILLATING SPINDLE SANDER

Product Dimensions:

Weight..... 86 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 26 x 26 x 39-1/2 in.
Footprint (Length x Width)..... 25-1/2 x 25 in.

Shipping Dimensions:

Type..... Cardboard
Content..... Machine
Weight..... 102 lbs.
Length x Width x Height..... 18 x 17 x 23 in.

Electrical:

Minimum Circuit Size..... 15 amp
Switch..... Toggle On/Off with Safety Locking Tab
Switch Voltage..... 110V
Cord Length..... 6 ft.
Cord Gauge..... 18 gauge
Plug Included..... Yes

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 1/2 HP
Voltage..... 110V
Prewired..... 110V
Phase..... Single
Amps..... 4.6A
Speed..... 3450 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer Direct Drive
Bearings..... Sealed and Permanently Lubricated

Main Specifications:

Table Info

Table Width..... 14-1/2 in.
Table Length..... 14-1/2 in.
Table Thickness..... 1 in.
Table Tilt..... 45 deg.
Table Opening..... 5-1/2 in.
Table Inserts..... 2-3/8 in.
Floor To Table Height..... 39-1/2 in.
Miter Gauge Slot Width..... 5/8 in.
Miter Gauge Slot Height..... 1/4 in.

Spindle Info

Spindle Diameter..... 2 in.
 Spindle Lengths..... 5-1/2 in.
 Spindle Speed..... 3450 RPM
 Spindle Oscillation..... 64 SPM
 Stroke Length..... 1 in.
 Arbor Size..... 15 mm
 Total Arbor Length..... 5 in.

Construction

Base..... Formed Steel
 Stand..... Steel
 Table..... Ground Cast Iron
 Frame..... Steel
 Miter Gauge..... Plastic
 Paint..... Epoxy

Other

No. Of Dust Ports..... 1
 Dust Port Size..... 2 in.
 Mobile Base..... G7314Z

Other Specifications:

Country Of Origin China
 Warranty 1 Year
 Serial Number Location Front Label
 Assembly Time 1 hour

Features:

Includes 80 Grit Sanding Sleeve, Miter Gauge and Wrench Set
 Table Tilts to 45 deg. for Bevel Sanding
 Steel Construction
 Cast Iron Table
 Paddle Safety Switch with Lock